

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>i30</i>	<i>i30</i> – Ice and Water Dispenser	i30
	Serial#: XC/IO200102P400/XXXX	

CONSUMABLES

FILTER	REPLACEMENT FREQUENCY	PART NUMBER
FIBER-CORE FILTER W/ PHOSPHATE	6 MONTHS, 10,000gal	ICE10K

SPECIFICATIONS

<u>ITEM</u>	<u>i30</u>
Water Connection	3/8" Quick Connect
Recommended Service Water Pressure	30-60psi (4.2-4.9kgf/cm ²)
Rate Voltage	AC 115V/60Hz @ 8.8Amps
Power Consumption	1.60kWh/24hrs
Power Cord	1.9m (6.3ft)
IP Class	IPX1
Climate Class	N Class (32°C +/- 1°C) (89.6°F +/- 33.8°F)
Safety Device	Overheating protector. Fuse.
Ice Storage Capacity	30lbs
Ice Production	380lbs/day @ 70°F air + 50°F water 289lbs/day @ 90°F air + 70°F water
Environmental Temperature	Max: 90°F (32°C) Min: 35°F (2°C)
Source Water Temperature	Max: 90°F (32.2°C) Min: 50°F(10°C)
Relative Humidity	55% at 78°F(25.5°C)
Refrigerant Gas	R-404A (400g) mfg on or before March 2024 R-404A (360g) mfg on or after April, 2024
R134a Pressures	375psi (25.8bar) High Side, 193psi (13.3bar) Low Side

SIZE SPECIFICATIONS

Dimension	i30 Ice/Water Unit	i30 Base Cabinet
Width/Depth/Height	16.6"W x 26.7"D x 46.1"H	16.6"W x 26.7"D x 28.3"H
Weight (dry)	223lbs	58lbs
Depth between legs (OD)	18.75"	N/A
Dispense Height	10.5"	N/A

