

## MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>i30</i>	<i>i30</i> – Ice and Water Dispenser	i30
	Serial#: XC/IO200102P401/XXXX (Post-2026 model, R290) Serial#: XC/IO200102P400/XXXX (Pre-2026 model, R404a)	

## CONSUMABLES

FILTER	REPLACEMENT FREQUENCY	PART NUMBER
FIBER-CORE FILTER W/ PHOSPHATE	6 MONTHS, 10,000gal	ICE10K

## SPECIFICATIONS

<u>ITEM</u>	<u>i30</u>
Water Connection	3/8" Quick Connect
Recommended Service Water Pressure	30-60psi (4.2-4.9kgf/cm <sup>2</sup> )
Rate Voltage	AC 115V/60Hz @ 8.0Amps
Power Consumption	1.60kWh/24hrs
Power Cord	1.9m (6.3ft)
IP Class	IPX1
Climate Class	N Class (32°C +/- 1°C) (89.6°F +/- 33.8°F)
Safety Device	Overheating protector. Fuse.
Ice Storage Capacity	30lbs
Ice Production	380lbs/day @ 70°F air + 50°F water 289lbs/day @ 90°F air + 70°F water
Environmental Temperature	Max: 90°F (32°C) Min: 35°F (2°C)
Source Water Temperature	Max: 90°F (32.2°C) Min: 50°F(10°C)
Relative Humidity	55% at 78°F(25.5°C)
R404a Version	
Refrigerant Gas	R404a (400g) mfg on or before March 2024 R404a (360g) mfg on or after April, 2025
R404a Pressures	375psi (25.8bar) High Side, 193 (13.3bar) Low Side
R290 Version	
Refrigerant Gas	R290 (3.49oz/99g)
R290 Pressures	300psig (20.7bar) High Side, 165psi (11.4bar) Low Side

**SIZE SPECIFICATIONS**

<b>Dimension</b>	<b>i30 Ice/Water Unit</b>	<b>i30 Base Cabinet</b>
Width/Depth/Height	16.6"W x 26.7"D x 46.1"H	16.6"W x 26.7"D x 28.3"H
Weight (dry)	223lbs	58lbs
Depth between legs (OD)	18.75"	N/A
Dispense Height	10.5"	N/A

